Domestic Declaration of Performance No. 012/HS/PHSC/2022

1. Construction product commercial name:

Hydrogard S

nydrophobizer

Hydrogard S

2. Construction product type designation:

Hydrogard S hydrophobic impregnation

3. Intended use(s)

Solvent hydrophobic preparation based on silanes and siloxanes for absorbent substrates

4. Manufacturer's name and address:

PHSC Chemicals Sp. z o.o. ul. Droga Dębińska 29 61-492 Poznań, Poland

5. Name and address of the authorised representative, should it be instituted:

N/A

- 6. National system used for assessment and verification of constancy of performance: **System 4**
- 7. National technical specification:
 - 7a. Polish product standard: N/A

Name of the accredited certification entity, accreditation number and national certificate number or name of the accredited laboratory (laboratories) and accreditation number: N/A

7b. National technical evaluation:

IBDIM NATIONAL TECHNICAL ASSESSMENT: No. IBDIM-KOT-2021/0749 Technical assessment entity/Domestic technical assessment entity:

Road and Bridge Research Institute

Name of the accredited certification entity, accreditation number and certificate number: Road and Bridge Research Institute, Anti-Corrosive Bridge Protection Team, No. Ab1424

8. Declared performance:

Essential characteristics of the construction product for intended use(s)	Declared performance	Procedure Test methods
Density	0,79 ± 5% g/cm ³	PN-EN ISO 12185:2002
Viscosity	1,99 ±10% mPa s	PN-EN ISO 3104:2004
Condition of the concrete surface after 200 cycles of freezing in the air and defrosting in water at: (-18±2)°C/(+18±2)°C	Coating unaltered	Procedure IBDIM nr PB/TM-1/13:2009



ul. Droga Dębińska 29, 61-492 Poznań, Poland mobile: 0048 693 861 115, 0048 601 77 88 23 www.phsc.pl, e-mail: biuro@phsc.pl www.antigraffiti-system.com

hydrophobizer	No. 012/HS/PHSC/2022	
Essential characteristics of the construction product for intended use(s)	Declared performance	Procedure Test methods
Capillary absorption	≤ 0,1 kg·m ⁻² ·h ^{-0.5}	PN-EN 1062-3:2008
Water absorption limit indicator	≥ 57 %	IBDIM Research Procedure Nr PB-TM-X5:2012
Impregnation depth	Class I < 10 mm	PN-EN 1504-2:2006

Domestic Declaration of Performance

9. The performance of the product identified above is in conformity with all the declared performance listed in point 8. This Domestic Declaration of Performance is issued pursuant to the Act of 16 April 2004 on construction products, under the sole responsibility of the manufacturer.

On behalf of the manufacturer signed by:

Hydrogard S

DYREKTOR TECHNICZNY Michał Mańkowski

[CHIEF TECHNICAL OFFICER] [MICHAŁ MAŃKOWSKI]

Name and surname and post

Poznań, 17.05.23 r. Place and date of issue



61-492 Poznań, ul. Droga Dębińska 29 tel. 601 77 88 22, 601 77 88 23 NIP 7831743569 REGON 364729733 www.phsc.pl



ul. Droga Dębińska 29, 61-492 Poznań, Poland mobile: 0048 693 861 115, 0048 601 77 88 23 www.phsc.pl, e-mail: biuro@phsc.pl www.antigraffiti-system.com